

Product Name: Metalium XDP 1800

Page: 1 of 5

This version issued: February, 2017

Section 1 - Identification of The Material and Supplier

Excision Pty Ltd

35 Peck St

Hamilton, Vic 3300

Phone: 1800 633 448 (office hours)

Fax: 03 5571 1944

sales@excision.com.au

Chemical nature: Water based preparation.

Trade Name: Metalium XDP 1800

Product Use: Bio Stable Water Soluble Lubricoolant.

Creation Date: October, 2014

This version issued: February, 2017 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria. **UN Number:** None allocated



GHS Signal word: WARNING

Serious eye irritation Category 2B

HAZARD STATEMENT:

H319: Causes serious eye irritation.

PREVENTION

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice.

STORAGE

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Pale brown liquid.

Odour: No data re odour.

Major Health Hazards: may cause serious damage to eyes.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc,%	TWA (mg/m³)	STEL (mg/m ³)
Tall oil fatty acid diethanolamide	68155-20-4	<10	not set	not set
Morpholine, 4,4'-methylenebis-	5625-90-1	<10	not set	not set

SAFETY DATA SHEET

Issued by: Excision Pty Ltd Phone: 1800 633 448 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Product Name: Metalium XDP 1800 Page: 2 of 5

This version issued: February, 2017

Diethanolamine 111-42-2 <10 13 not set Water 7732-18-5 to 100 not set not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness.

Fire decomposition products from this product are likely to be irritating if inhaled.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: Does not burn.

Upper Flammability Limit: Does not burn.

Lower Flammability Limit: Does not burn.

Autoignition temperature: Not applicable - does not burn.

Flammability Class: Does not burn.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to



Product Name: Metalium XDP 1800

Page: 3 of 5

This version issued: February, 2017

disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³) STEL (mg/m³)
Diethanolamine 13 not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a

fan is suggested. **Eye Protection:** Protective glasses or goggles must be worn when this product is being used. Failure to protect

your eyes may lead to severe harm to them or to general health. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Pale brown liquid.

Odour: No data re odour.

Boiling Point: Approximately 100°C at 100kPa.

Freezing/Melting Point: Below 0°C.

Volatiles: Water component.

Vapour Pressure: 2.37 kPa at 20°C (water vapour pressure).

Vapour Density: As for water. Specific Gravity: No data.

Water Solubility: Completely soluble in water.

pH: No data.

Volatility: No data.

Odour Threshold: No data.

Evaporation Rate: As for water.

Coeff Oil/water Distribution: No data

Autoignition temp: Not applicable - does not burn.



Product Name: Metalium XDP 1800

Page: 4 of 5

This version issued: February, 2017

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed

Incompatibilities: strong acids, acid chlorides, acid anhydrides and chloroformates.

Fire Decomposition: Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

Diethanolamine >=5%Conc<10%: Xi; R36

4,4'-METHYLENEDIMORPHOLINE

7 patients reacted positively to the formaldehyde releaser 4,4'-methylenebismorpholine, and 6 of these patients also reacted to formaldehyde and/or other formaldehyde releasers. 4 patients reacted positively to myristyl alcohol tested at 10% petrolatum (pet.). Additionally, 20 doubtful or irritant reactions occurred. 1 patient each reacted positively to oleyl alcohol, MIPA, and AEPD. Conclusions: 4,4'-methylenebis morpholine may be an important MWF allergen, although clinical relevance could not be stated definitely in every case.

Convulsions, tumours at sites of application, peripheral nerve tumours recorded. Equivocal tumourigen by RTECS criteria.

DIETHANOLAMINE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.

TALL OIL FATTY ACIDS, DIETHANOLAMIDE, 4,4'-METHYLENEDIMORPHOLINE

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is a severe eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms such as swelling of eyelids and blurred vision may also

SAFETY DATA SHEET

Issued by: Excision Pty Ltd Phone: 1800 633 448 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Product Name: Metalium XDP 1800 Page: 5 of 5

This version issued: February, 2017

become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment is likely to cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product may be

irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP.

IARC: Diethanolamine is classed 2b IARC - possibly carcinogenic to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

Insufficient data to be sure of status.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle product and containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS
SWA
Australian Inventory of Chemical Substances
Safe Work Australia, formerly ASCC and NOHSC
CAS number
Chemical Abstracts Service Registry Number
International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, February, 2017.

http://www.kilford.com.au/ Phone (02)9251 4532

SAFETY DATA SHEET

Issued by: Excision Pty Ltd Phone: 1800 633 448 (office hours)