PROMAX 350 WELDING HELMET

Updated 25.06.2025



Ultra-Clear Vision

4 Arc Sensors

for reliable arc detection & switching

Generous Viewing Area

Larger than many other helmets in this class (100 x 53mm)

Reliable Power Source

Replaceable battery, solar assist, efficient electronics for low power consumption

Magnification Lens Holder

Lightweight & Comfortable

AS1337.1 High-Impact Rated A must for many work sites

Grind-Mode

Locks the lens in light shade at the flick of a switch.



Shade, Sensitivity & **Delay Adjustments**

Precise & easy-to-use controls

- Ideal for MIG & Stick Welding, also suits TIG welding down to 30 amps
- Fast & easy cover lens replacement
- "Full Laminate" lens construction: Each layer in lens assembly is laminated for superior optical quality and reliability
- · Bonus helmet bag









Weldclass

PROMAX 350 WELDING HELMET

Updated 25.06.2025



Ordering & Parts Information			
Item	Part No.	Item	Part No.
Helmet Promax 350 Blue	WC-05313	Magnification Lens 1.5x	P7-ML15
Helmet Promax 350 Aussie	WC-05315	Magnification Lens 2.0x	P7-ML20
Lens Kit 2 Outer + 1 Inner	WC-05335	Magnification Lens 2.5x	P7-ML25
Cover Lens Inner 106x59mm Pk 5	WC-05321	Sweatbands Pk5	WC-01630
Cover Lens Outer 115x104mm Pk 10	WC-05323	Battery CR2032	Available from most battery retailers
Headgear Assembly	WC-05325		

Technical Data		
Applications	MIG, MMA/Stick & TIG (≥30 amps), Grinding, Plasma Cutting, Arc-Air Gouging	
Switching Speed	Conforms to & exceeds requirements of AS/NZS 1338.1 Standard	
Arc Sensing	4 Sensors	
TIG Optimised	Yes. Suitable for low-amp TIG down to 30 amps	
Power Supply	1 x CR2032 replaceable battery & solar assist	
On / Off	Ready to use at any time, no switching required	
Inactive Shade (Grind/Off)	Shade 4	
Active Shade (Weld)	Dual Range 5-8 / 9-13	
Sensitivity	Low – High	
Delay	0.1 - 1.0 seconds	
Grind Mode	Switchable On/Off	
Weight	480g	
Viewing Area	100x53mm	
Magnification Lens Holder	Takes standard 108x51mm Magnification Lenses	
Standards Compliance	Lens: AS/NZS1338.1, EN379, ANSI Z87.1, CSA Z94.3 Shell: AS/NZS1337.1 High Impact EN 175 B, ANSI Z87.1, CSA Z94.3	
Optical Rating	1/1/1/2 (Optical quality / Diffusion of light / Variation in luminous transmittance / Angle dependency)	
Warranty	Conditional 7 years (on auto darkening lens) See Weldclass.com/warrantyinfo for details	
Temperature Range	Operating -5 °C to +55 °C / Storage -10 to +65 °C	



